

Applique



cod. 50APP3000K

Descrizione / Description

Applique da incasso a muro o a pannello
con sorgente luminosa orientabile

Reading lamp mountable on wall or on a panel with
orientable light



Caratteristiche

- materiale: **ottone**
- dimensioni: **L128 H54 P25 mm**
- taglio perimetrale: **diritto o bisellato**
- grado di protezione (IP): **IP21**
- tipo di montaggio: **incassato a muro o a pannello, sia verticale che orizzontale**
- sorgente luminosa: **luce calda 3000K, 180lm**
- trasformatore: **incluso, caratteristiche input: 230V 50hz output: 6V 350mA 1,5W**
- marchio: **CE**
- note di installazione: **per il montaggio a muro è necessaria la cassaforma opzionale, per il montaggio a pannello è sufficiente prevedere un foro rettangolare da 100x32mm e 65mm di profondità**



Features

- material: **brass**
- measurements: **L128 H54 P25**
- edge cutting: **straight or bevelled**
- degree of protection (IP): **IP21**
- type of mounting: **recessed into the wall or in a panel, mountable both vertically and horizontally**
- light: **warm light 3000K, 180lm**
- driver: **included, features input: 230V 50hz output: 6V 350mA 1,5W**
- marking: **CE**
- installing notes: **for wall mounting it is necessary the optional formwork, instead for panel mounting it is enough to realize a rectangular hole 100x32mm and 65mm of depth**

Disegni / Drawings

